



#### PHONES

(044) 338-0-130  
 (050) 332-0-130  
 (063) 577-0-130  
 (067) 353-0-130

**130**  
 COM.UA

Internet store of  
 autogoods



SKYPE  
 km-130

CAR RECEIVERS — Receivers • Media receivers and stations • Native receivers • CD/DVD changers • FM-modulators/USB adapters • Flash memory • Facia plates and adapters • Antennas • Accessories |  
 CAR AUDIO — Car audio speakers • Amplifiers • Subwoofers • Processors • Crossovers • Headphones • Accessories | TRIP COMPUTERS — Universal computers • Model computers • Accessories |  
 GPS NAVIGATORS — Portable GPS • Built-in GPS • GPS modules • GPS trackers • Antennas for GPS navigators • Accessories | VIDEO — DVR • TV sets and monitors • Car TV tuners • Cameras • Videomodules  
 • Transcoders • Car TV antennas • Accessories | SECURITY SYSTEMS — Car alarms • Bike alarms • Mechanical blockers • Immobilizers • Sensors • Accessories | OPTIC AND LIGHT — Xenon • Bixenon • Lamps  
 • LED • Stroboscopes • Optic and Headlights • Washers • Light, rain sensors • Accessories | PARKTRONICS AND MIRRORS — Rear parktronic • Front parktronic • Combined parktronic • Rear-view mirrors  
 • Accessories | HEATING AND COOLING — Seat heaters • Mirrors heaters • Screen-wipers heaters • Engine heaters • Auto-refrigerators • Air conditioning units • Accessories | TUNING — Vibro-isolation  
 • Noise-isolation • Tint films • Accessories | ACCESSORIES — Radar-detectors • Handsfree, Bluetooth • Windowlifters • Compressors • Beeps, loudspeakers • Measuring instruments • Cleaners • Carsits  
 • Miscellaneous | MOUNTING — Installation kits • Upholstery • Grilles • Tubes • Cable and wire • Tools • Miscellaneous | POWER — Batteries • Converters • Start-charging equipment • Capacitors  
 • Accessories | MARINE AUDIO AND ELECTRONICS — Marine receivers • Marine audio speakers • Marine subwoofers • Marine amplifiers • Accessories | CAR CARE PRODUCTS — Additives • Washer fluid •  
 Care accessories • Car polish • Flavors • Adhesives and sealants | LIQUID AND OIL — Motor oil • Transmission oil • Brake fluid • Antifreeze • Technical lubricant



In store "130" you can find and buy almost all necessary goods for your auto in Kyiv and other cities, delivery by ground and postal services. Our experienced consultants will provide you with exhaustive information and help you to chose the very particular thing. We are waiting for you at the address

<http://130.com.ua>


Integration module  
Model Name: **Ajax Transmitter**

Module for third-party detector integration

The Transmitter is a module for connecting third-party detectors to the Ajax security system. It transmits alarms and anti-tampering signals from external detectors; a built-in accelerometer protects it from dismounting. The module operates on batteries and can power the connected detector. The communication range can be up to 1,600 meters provided that there are no obstacles and the case is removed.

**IMPORTANT:** This Quick Start Guide contains general information about the Transmitter. Before using the device, we recommend to reviewing the User Manual on the website: [ajax.systems/support/devices/transmitter](https://ajax.systems/support/devices/transmitter)

## FUNCTIONAL ELEMENTS



1. QR code.
2. Battery contacts.
3. Light indicator.
4. On/off button.
5. Power terminals for the detector, alarm and anti-tampering signals.

## IMPORTANT INFORMATION

This product can be used across all EU member states.

This device in compliance with the essential requirements and other relevant provisions of Directive 2014/53/EU. All essential radio test suites have been carried out.

## CONNECTING AND SETTING UP

The Transmitter can only be connected to the Ajax security system, it is not compatible with Ajax ocBridge Plus or Ajax uartBridge.

The Transmitter is connected to the Hub and set up via the Ajax Security system mobile application. To establish connection please locate the module and the Hub within the communication range and follow the device adding procedure.

### Set the following parameters in the Transmitter settings:

**The state of the external detector contact**, which can be normally closed or normally open.

**The type (mode) of the external detector** that can be bistable or pulse.

**The state of the anti-tamper switch**, which can be normally closed or normally open.

**The accelerometer-triggered alarm** — you can turn this signal off or on.

### Select the power mode for the external detector.

**Turned off when the Hub is not armed** — the module stops powering the external detector upon disarming and does not process signals from the ALARM terminal. When arming the detector, the power supply resumes, but the alarm signals are ignored for the first 8 seconds.

**Always off** — the Transmitter saves energy by turning off the power of the external detector. The signals from the ALARM terminal are processed both in the pulse and bistable modes.

**Always on** — this mode should be used if there are any problems in the "Turned off when the Hub is not armed" mode. When the security system is armed, signals from the ALARM terminal are processed no more than once in three minutes in the pulse mode. If the bistable mode is selected, such signals are processed instantly.

If the **"24 hours" operating mode** is selected for the module, the external detector is powered only in the "Always on" or the "Turned off when the Hub is not armed" mode, regardless of the security system status.

## COMPLETE SET

1. Transmitter.
2. 3 x CR123A batteries.
3. User Manual.
4. Installation kit.

## LOCATION SELECTION

The Transmitter should be located inside the case of the third-party detector. The module with mounting rack requires space with the following minimum dimensions: 100 x 39 x 29 mm. If the Transmitter can not be installed inside the case of the detector itself, you should use any available radio frequency-transparent case.

When choosing a location for a detector with the Transmitter module, take into account the presence of any obstacles impairing radio signal transmission.


Prior to the attachment of the detector to a surface with screws, please perform signal level test in the Ajax Security System application for at least a minute.

| Status indicator                                  |  | Signal level           |
|---|--|------------------------|
| Lights with interruptions once every 1.5 seconds  |  | Excellent signal level |
| Blinks 5 times per second                         |  | Good signal level      |
| Blinks 2 times per second                         |  | Bad signal level       |
| Lights up for a short time once every 1.5 seconds |  | No signal              |

## INSTALLING AND CONNECTING THE DETECTOR

1. Connect the Transmitter to the NC/NO (select the appropriate setting in the app) and COM contacts of the detector.

Function of the Transmitter Terminals:



| Power |   | ALARM |     | TAMPER |     |
|-------|---|-------|-----|--------|-----|
| +     | - | NC/NO | COM | NC/NO  | COM |

2. Secure the Transmitter inside the detector case. It is recommended to use the plastic stands that are included in the Transmitter installation kit.

## TECH SPECS

|   |                                      |
|---|--------------------------------------|
| Connecting a detector                               | ALARM and TAMPER (NO/NC) terminals   |
| Mode for processing alarm signals from the detector | Pulse or Bistable                    |
| Power   | 3 x CR123A, 3V batteries             |
| Capability to power the connected detector          | Yes, 3.3V                            |
| Protection from dismounting                         | Accelerometer                        |
| Frequency band                                      | 868.0-868.6 mHz                      |
| Maximum RF output power                             | Up to 20 mW                          |
| Modulation  | FM                                   |
| Communication range                                 | Up to 1,600 m (any obstacles absent) |
| Ping interval for the connection with the receiver  | 12–300 sec                           |
| Operating temperature                               | From -25°C to +50°C                  |
| Operating humidity                                  | Up to 80%                            |
| Dimensions  | 100 x 39 x 22 mm                     |
| Weight  | 74 g                                 |

## WARRANTY

Warranty for the Ajax Systems Inc. devices is valid for 2 years after the purchase and does not apply to the supplied battery. If the device does not work correctly, you should first contact the support service—in half of the cases, technical issues can be solved remotely!

The full text of the warranty is available on the website:

[ajax.systems/warranty](https://ajax.systems/warranty)

User Agreement:

[ajax.systems/end-user-agreement](https://ajax.systems/end-user-agreement)

Technical support:

[support@ajax.systems](mailto:support@ajax.systems)



CAUTION: RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE. DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS