

PHONES (044) 360-7-130 (050) 336-0-130 (063) 788-0-130 (067) 233-0-130 (068) 282-0-130

Internet store of autogoods

•

294-0-130 597-0-130

> SKYPE km-130

CAR RECEIVERS — Receivers • Media receivers and stations • Native receivers • CD/DVD changers • FM-modulators/USB adapters • Flash memory • Facia plates and adapters • Antennas • Accessories |

CAR AUDIO — Car audio speakers • Amplifiers • Subwoofers • Processors • Crossovers • Headphones • Accessories | TRIP COMPUTERS — Universal computers • Model computers • Accessories |

GPS NAVIGATORS — Portable GPS • Built-in GPS • GPS modules • GPS trackers • Antennas for GPS navigators • Accessories | VIDEO — DVR • TV sets and monitors • Carr TV tuners • Cameras • Videomodules
• Transcoders • Carr TV antennas • Accessories | SECURITY SYSTEMS — Car alarms • Bike alarms • Mechanical blockers • Immobilizers • Sensors • Accessories | OPTIC AND LIGHT — Xenon • Bixenon • Lamps
• LED • Stroboscopes • Optic and Headlights • Washers • Light, rain sensors • Accessories | PARKTRONICS AND MIRRORS — Rear parktronics • Combined parktronics • Rear-view mirrors
• Accessories | HEATING AND COOLING — Seat heaters • Mirrors heaters • Screen-wipers heaters • Engine heaters • Auto-refrigerators • Air conditioning units • Accessories | TUNING — Vibro-isolation
• Noise-isolation • Tint films • Accessories | ACCESSORIES — Radar-detectors • Handsfree, Bluetooth • Windowlifters • Compressors • Beeps, loudspeakers • Measuring instruments • Cleaners • Carsits
• Miscellaneous | MOUNTING — Installation kits • Upholstery • Grilles • Tubes • Cable and wire • Tools • Miscellaneous | POWER — Batteries • Converters • Start-charging equipment • Capacitors
• Accessories | MARINE AUDIO AND ELECTRONICS — Marine receivers • Marine audio speakers • Marine subwoofers • Marine amplifiers • Accessories | CAR CARE PRODUCTS — Additives • Washer fluid • Care accessories • Car polish • Flavors • Adhesives and sealants | LIQUID AND OIL — Motor oil • Transmission oil • Brake fluid • Antifreeze • Technical lubricant



In store "130" you can find and buy almost all necessary goods for your auto in Kyiv and other cities, delivery by ground and postal services. Our experienced consultants will provide you with exhaustive information and help you to chose the very particular thing. We are waiting for you at the address

http://130.com.ua



HERTZ

www.hertzaudiovideo.eu





EGEND

MLK 165.3

SYSTEM

300 W


TECHNICAL SPECIFICATIONS

Component		2-way system
Size		
Woofer	mm (in.)	165 (6.5)
Tweeter diaphragm	mm (in.)	35 (1.38)
Crossover	mm (in.) 146 x 114 x 40 (5.74 x 4.49 x 1.57)	
Voice Coil Ø		
Woofer	mm (in.)	36 (1.4)
Tweeter	mm (in.)	28 (1.1)
Power Handling	W peak	300
_	W continuos	150
Impedance	Ω	4
Frequency Response	Hz	40 ÷ 25k
Crossover cut-off	Lo/Hi-pass	3.5 kHz -12 dB Oct
Crossover adjustment	Tweeter Level	+2 / 0 / -2 dB
	Hi-Contour	ON / OFF
Weight of one component	:	
Woofer	kg (lb)	1,65 (3.64)
Tweeter	kg (lb)	0,075 (0.16)
Crossover	kg (lb)	0,37 (0.82)

ELECTRO-ACOUSTIC PARAMETERS

MLCX 165.3: Tweeter-Level

		IVIL 165.3	ML 28.3
D	mm	132	28
Xmax	mm	±5	<i>)</i>
Re	Ω	3,3	3,3
Fs	Hz	65	900
Le	mH	0,37	0,024
Vas	1	9	-
Mms	g	17	0,4
Cms	mm/N	0,3	0,08
BL	T∙m	6	2
Qts		0,57	1,1
Qes		0,64	1,7
Qms		5,4	3,3
Spl	dB	92	91



Frequency (Hz)



ML 28.3 Legend

- Double Neodymium magnet optimized with FEA simulations, for maximum field symmetry and exceptional transfer efficiency.
- 2. Tetolon Fiber dome optimized with FEA simulations, for excellent dynamics and angle dispersion.
- 3. Larger rear chamber, to reduce Fs from 1000Hz to 900Hz.
- Natural fibre non-woven sound-absorption material, for better damping and more natural acoustic emission.

ML 165.3 Legend

- CCAW double-layer 36 mm voice coil on Kapton former, for exceptional power handling and no-compromise dynamics.
- 2. Exponential V-cone® with optimized geometry for better dispersion and higher SPL performance.
- 3. "Boundary Free" IIR rubber surround, for higher efficiency.
- 4. Cotton-injected paper cone for stiffness, lightweight and dynamics.
- 5. Three-spoke, anti-resonant aluminium alloy basket featuring built-in venting holes.
- 6. Highly acoustic transparent basket design

MLCX 165.3 Legend

- "Hi-Contour" two-position control, to select the tweeter hi-pass crossover point according to the tweeter position/angle towards the listener.
- 2. Three terminals for tweeter level adjustment in 2 dB steps, to fine-tune the transducer's emission.
- Extremely high quality bi-metallized 160V polyester film capacitors with ultra-low DF, for maximum sound transparency and neat mid/hi-frequencies.
- 4. Air wound built on pure copper-wire copper-wire with up to 1mm diameter, for high saturation threshold of the magnetic flux and low losses on the woofer section where high transient currents are demanded.
- 5. High power rating Wirewound resistors, to ensure performance stability even at high operating temperature. The Wirewound build construction grants low parasitic series inductance thus reducing losses at high frequencies, especially for resistors in series to the tweeter.

MLCX 165.3: Hi-Contour

