

PHONES (044) 360-7-130 (050) 336-0-130 (063) 788-0-130 (067) 233-0-130 (068) 282-0-130

130 Internet store of autogoods



294-0-130 597-0-130

> SKYPE km-130

CAR RECEIVERS — Receivers • Media receivers and stations • Native receivers • CD/DVD changers • FM-modulators/USB adapters • Flash memory • Facia plates and adapters • Antennas • Accessories |

CAR AUDIO — Car audio speakers • Amplifiers • Subwoofers • Processors • Crossovers • Headphones • Accessories | TRIP COMPUTERS — Universal computers • Model computers • Accessories |

GPS NAVIGATORS — Portable GPS • Built-in GPS • GPS modules • GPS trackers • Antennas for GPS navigators • Accessories | VIDEO — DVR • TV sets and monitors • Carr TV tuners • Cameras • Videomodules
• Transcoders • Carr TV antennas • Accessories | SECURITY SYSTEMS — Car alarms • Bike alarms • Mechanical blockers • Immobilizers • Sensors • Accessories | OPTIC AND LIGHT — Xenon • Bixenon • Lamps
• LED • Stroboscopes • Optic and Headlights • Washers • Light, rain sensors • Accessories | PARKTRONICS AND MIRRORS — Rear parktronics • Combined parktronics • Rear-view mirrors
• Accessories | HEATING AND COOLING — Seat heaters • Mirrors heaters • Screen-wipers heaters • Engine heaters • Auto-refrigerators • Air conditioning units • Accessories | TUNING — Vibro-isolation
• Noise-isolation • Tint films • Accessories | ACCESSORIES — Radar-detectors • Handsfree, Bluetooth • Windowlifters • Compressors • Beeps, loudspeakers • Measuring instruments • Cleaners • Carsits
• Miscellaneous | MOUNTING — Installation kits • Upholstery • Grilles • Tubes • Cable and wire • Tools • Miscellaneous | POWER — Batteries • Converters • Start-charging equipment • Capacitors
• Accessories | MARINE AUDIO AND ELECTRONICS — Marine receivers • Marine audio speakers • Marine subwoofers • Marine amplifiers • Accessories | CAR CARE PRODUCTS — Additives • Washer fluid • Care accessories • Car polish • Flavors • Adhesives and sealants | LIQUID AND OIL — Motor oil • Transmission oil • Brake fluid • Antifreeze • Technical lubricant



In store "130" you can find and buy almost all necessary goods for your auto in Kyiv and other cities, delivery by ground and postal services. Our experienced consultants will provide you with exhaustive information and help you to chose the very particular thing. We are waiting for you at the address

http://130.com.ua

OCE AV K5 TWO WAY SYSTEM

- **TWEETER**1 Tetolon® dome, a combination of silk and cotton with proprietary damping treatment, provides low mass and resonance-free response up to ultrasonic frequencies.
- 2 CCAW (Copper Clad Aluminium Wire) voice coil wound on double layer, extremely lightweight and compact, resulting very high efficiency and a
- 3 The annular geometry of the Rear Damping Chamber, together with the proprietary damping material, extends the frequency response to lower limits and reduces harmonic distortion.
- 4 High flux density Neodymium magnet, for very high efficiency and dynamic sound.

WOOFER

- The profile of the aerodynamic basket's spokes, along with the "open-air" design, ensures drastic reduction of back-wave reflections.

 The exclusive Triple Wave surround profile and selected materials provide full linearity as well as reliable performance.
- Extremely lightweight and compact, the CCAW (Copper Clad Aluminium Wire) voice coils provide very high efficiency and optimum thermal dissipation.
- Cotton-fibre pressed paper cone with Light Damping treatment. The Radial Venting System ensures high thermal capability, power handling and reliability.

PASSIVE CROSSOVER

Especially designed for the AV K5 and AV K6 two-way complete systems, shapes their acoustic response to achieve a consistent, harmonious sound in any vehicle, also offering the acoustic controls necessary to achieve the best balance according to one's own taste.

TECHNICAL SPECIFICATIONS

Component		2 way system
Size mm	AV 5.0 Woofer AV 1.1 Tweeter	130 (5" ^{1/4}) 28 (1" ^{1/8})
Power Handling		
· ·	W Peak	200
	W continuous	100
Impedance	Ohm	4
Frequency Response	Hz	60 ÷ 22k
Sensitivity	dB/SPL	90
Crossover included	LO/HI PASS	2.5 kHz @ 12/12 dB Oct.
Componet adjustment	Tweeter	+2; 0; -2 dB
Outer Ø	Woofer	131
mm	Tweeter	48
Mounting Ø	Woofer	115
mm	Tweeter	44,8
Total depth	Woofer	71
mm	Tweeter	28
Mount. depth	Woofer	65
mm	Tweeter	15,2
Magnet size	Woofer	90
mm	Tweeter	27,9
Weight of one	Woofer	1,125
component kg	Tweeter	0,073
Voice Coil Ø	Woofer	25
mm	Tweeter	28





ELECTRO-ACOUSTIC PARAMETERS

D	mm	103
Xmax	mm	3
Re	Ohm	3,5
Fs	Hz	81
Le	mH @ 1 kHz	0,26
Le	mH @ 10 kHz	0,17
Vas	I	3,14
Mms	g	11,2
Cms	mm/N	0,33
BL	T-m	5,05
Qts		0,73
Qes		0,80
Qms		8,91
Spl	dB	90