



PHONES

(044) 360-7-130
(050) 336-0-130
(063) 788-0-130
(067) 233-0-130
(068) 282-0-130

130
COM.UA

Internet store of
autogoods



ICQ
294-0-130
597-0-130

SKYPE
km-130

CAR RECEIVERS — Receivers • Media receivers and stations • Native receivers • CD/DVD changers • FM-modulators/USB adapters • Flash memory • Facia plates and adapters • Antennas • Accessories |
CAR AUDIO — Car audio speakers • Amplifiers • Subwoofers • Processors • Crossovers • Headphones • Accessories | TRIP COMPUTERS — Universal computers • Model computers • Accessories |
GPS NAVIGATORS — Portable GPS • Built-in GPS • GPS modules • GPS trackers • Antennas for GPS navigators • Accessories | VIDEO — DVR • TV sets and monitors • Car TV tuners • Cameras • Videomodules
• Transcoders • Car TV antennas • Accessories | SECURITY SYSTEMS — Car alarms • Bike alarms • Mechanical blockers • Immobilizers • Sensors • Accessories | OPTIC AND LIGHT — Xenon • Bixenon • Lamps
• LED • Stroboscopes • Optic and Headlights • Washers • Light, rain sensors • Accessories | PARKTRONICS AND MIRRORS — Rear parktronic • Front parktronic • Combined parktronic • Rear-view mirrors
• Accessories | HEATING AND COOLING — Seat heaters • Mirrors heaters • Screen-wipers heaters • Engine heaters • Auto-refrigerators • Air conditioning units • Accessories | TUNING — Vibro-isolation
• Noise-isolation • Tint films • Accessories | ACCESSORIES — Radar-detectors • Handsfree, Bluetooth • Windowlifters • Compressors • Beeps, loudspeakers • Measuring instruments • Cleaners • Carsits
• Miscellaneous | MOUNTING — Installation kits • Upholstery • Grilles • Tubes • Cable and wire • Tools • Miscellaneous | POWER — Batteries • Converters • Start-charging equipment • Capacitors
• Accessories | MARINE AUDIO AND ELECTRONICS — Marine receivers • Marine audio speakers • Marine subwoofers • Marine amplifiers • Accessories | CAR CARE PRODUCTS — Additives • Washer fluid •
Care accessories • Car polish • Flavors • Adhesives and sealants | LIQUID AND OIL — Motor oil • Transmission oil • Brake fluid • Antifreeze • Technical lubricant



In store "130" you can find and buy almost all necessary goods for your auto in Kyiv and other cities, delivery by ground and postal services. Our experienced consultants will provide you with exhaustive information and help you to chose the very particular thing. We are waiting for you at the address

<http://130.com.ua>

SUB Mille

WOOFER

ML 3000 1500 watt

Technical Specifications

Component	Subwoofer	
Size	mm	300 (12")
Power Handling (Watt)	peak	1500
	continuous program	750
Impedance	Ohm	4
Frequency response	Hz	25-900
Sensitivity	dB/SPL	89
Outer diameter	mm	318
Mounting hole diameter	mm	284
Total depth	mm	207
Mounting depth	mm	179
Total driver displacement	lit	3,1
Weight of one component	kg	12,8
Voice coil diameter	mm	65
Magnet	Double magnet high density flux ferrite	
Cone	Polypropylene with mineral powder	
Xmech*	mm	28

Electro-Acoustic Parameters



D	mm	253
Xmax	mm	19
Re	ohm	2,6
Fs	Hz	32
Le	mH@1kHz	1,67
Le	mH@10kHz	0,83
Vas	lit	39
Mms	gr	197
Cms	mm/N	0,12
BL	T-m	14
Qts		0,51
Qes		0,53
Qms		10,40
Spl (1m/2,83V)	dB	89



Powerful from the lowest octaves of the audio range. The Hertz ML subs set a new benchmark for low frequency reproduction with the impact, dynamics and pressure that only a reference component can achieve.

Power and harmony in the anti-resonant aluminium alloy basket design, self-standing low incidence five-spokes structure, Front-Back Gasket, magnet protection.

Ultimate technology in every detail: V-CONE with Polypropylene membrane stiffened with mineral dusts, high excursion surrounds, extended pole piece, dual layer mobile voice coil with copper covered aluminium wire (CCAW), oversize motor assembly with an exclusive forced ventilation circuit. A harder, deeper and more controlled bass for a unique enthralling experience.



* Xmech maximum mechanic excursion: it indicates the motion range in the speaker linear functioning area, in both ways.



ML 3000



V-Cone® Subwoofer

The V-CONE is applied to a Polypropylene membrane stiffened with mineral dusts. The exponential profile without dust cover gets very close to the ideal one and eliminates break-ups to provide the maximum undistorted performance.





Anti-Resonant Alloy Basket

Reference in design: power and harmony in a mix of sharp lines and widely curved profiles. The anti-resonant aluminium alloy basket features five low incidence spokes and offers the minimum back radiation resistance, eliminating every distortion due to acoustic compression. The self-standing geometry of the structure contributes to total mechanical damping, performing a perfectly transparent sound.

Triple Venting System

The combination of flared port with radial holes in the central pole in the bottom plate carries the air compressed by the cone movement directly to the mobile voice coil and outside the magnet assembly, producing a 30% fall of the speaker operation temperature.

The improvement of the air flows inside the motor, with this peculiar channel geometry, creates a forced ventilation circuit that drastically reduces the dynamic compression, raising the applicable power over the top.



Symmetrical Shape Pole

The "Symmetrical Shape" central pole addresses the external lines increasing the magnetic flux density and perceptibly decreasing the field asymmetry distortion.

An aluminium rounded ring inside the motor cuts the inductance modulation at the highest excursions, for a harder, deeper, clearer bass.

Front Back Gasket

Basic design and care for details. The gasket is designed to allow both possible mountings.

In the traditional position a rubber gasket ensures a perfect hermetical seal and the inserts, imitating the spokes lines, protect and cover the subwoofer fixing screws. When the sub is used with the magnet visible, the gasket can be mounted upside down in order to finish off the basket nicely.



FRONT BACK GASKETS