



PHONES

0 (800) 800 130
(050) 462 0 130
(063) 462 0 130
(067) 462 0 130

130
COM.UA

Internet store of
autogoods



SKYPE

km-130

CAR RECEIVERS — Receivers • Media receivers and stations • Native receivers • CD/DVD changers • FM-modulators/USB adapters • Flash memory • Facia plates and adapters • Antennas • Accessories |
CAR AUDIO — Car audio speakers • Amplifiers • Subwoofers • Processors • Crossovers • Headphones • Accessories | TRIP COMPUTERS — Universal computers • Model computers • Accessories |
GPS NAVIGATORS — Portable GPS • Built-in GPS • GPS modules • GPS trackers • Antennas for GPS navigators • Accessories | VIDEO — DVR • TV sets and monitors • Car TV tuners • Cameras • Videomodules
• Transcoders • Car TV antennas • Accessories | SECURITY SYSTEMS — Car alarms • Bike alarms • Mechanical blockers • Immobilizers • Sensors • Accessories | OPTIC AND LIGHT — Xenon • Bixenon • Lamps
• LED • Stroboscopes • Optic and Headlights • Washers • Light, rain sensors • Accessories | PARKTRONICS AND MIRRORS — Rear parktronic • Front parktronic • Combined parktronic • Rear-view mirrors
• Accessories | HEATING AND COOLING — Seat heaters • Mirrors heaters • Screen-wipers heaters • Engine heaters • Auto-refrigerators • Air conditioning units • Accessories | TUNING — Vibro-isolation
• Noise-isolation • Tint films • Accessories | ACCESSORIES — Radar-detectors • Handsfree, Bluetooth • Windowlifters • Compressors • Beeps, loudspeakers • Measuring instruments • Cleaners • Car seats
• Miscellaneous | MOUNTING — Installation kits • Upholstery • Grilles • Tubes • Cable and wire • Tools • Miscellaneous | POWER — Batteries • Converters • Start-charging equipment • Capacitors
• Accessories | MARINE AUDIO AND ELECTRONICS — Marine receivers • Marine audio speakers • Marine subwoofers • Marine amplifiers • Accessories | CAR CARE PRODUCTS — Additives • Washer fluid •
Care accessories • Car polish • Flavors • Adhesives and sealants | LIQUID AND OIL — Motor oil • Transmission oil • Brake fluid • Antifreeze • Technical lubricant



In store "130" you can find and buy almost all necessary goods for your auto in Kyiv and other cities, delivery by ground and postal services. Our experienced consultants will provide you with exhaustive information and help you to chose the very particular thing. We are waiting for you at the address

<https://130.com.ua>



Elate Carbon Installation Guide

Elate Carbon / Pro

52, 62, 53, 63, 93, 52A,
62A, 53A, 63A, 93A

Components

Alto tweeter, MT450,
MW5, MW6, MW9, MM3,
MXT280C, MXT380C






Dear Customer,



Thank you for choosing Morel for your car audio speaker solution. Morel prides itself on engineering and producing the best high-fidelity speaker systems. We hope you enjoy your Elate Carbon speakers for years to come. If you have any questions, please contact your Morel dealer or Morel support at: www.morelhifi.com

Elate Carbon Components


Elate Carbon MW5, MW6, and MW9 Woofer




MT450 Tweeter





MXT380c/MXT280c Crossover



Alto Tweeter (PRO line only)




MM3 Midrange




Woofers, Midrange and Alto Tweeter mounting


MW6 woofer




MW5 and MW9 woofer



MM3




Alto Tweeter



MT450 Tweeter and Crossover Mounting


MT450 Flush Mount



MT450 Surface Mount






Crossover mounting



Crossover Connections




2-WAY Systems Crossover

- ① Standard wire connection/
With bridged jumpers
- ② Bi wire connection/
No bridged jumpers
- ③ Bi Amp connection/
No bridged jumpers




3-WAY Systems Crossover


- ① Standard wire connection/
With bridged jumpers
- ② Bi wire connection/
No bridged jumpers
- ③ Bi Amp connection/
No bridged jumpers



2-WAY Crossover Alignment System



3-WAY Crossover Alignment System



Specifications

WOOFERS	ELATE CARBON MM3	ELATE CARBON MW5	ELATE CARBON MW6	ELATE CARBON MW9
Nominal Impedance (ohm)	4	4	4	4
Power Handling Wrms	120	160	180	200
Max. Trans. Pwr Handling Wrms	400	1000	1000	1000
Sensitivity (2.83 V/1M) dB	85	85	87	89
Frequency response Hz	40-6000	40-5000	30-4000	25-3000
Resonant Freq. Fs Hz	93.6	64.4	45	44
Voice Coil Diameter mm (inch)	54 (2.125)	75 (3)	75 (3)	75 (3)
Voice Coil Height mm (inch)	10 (0.4)	14.50 (0.57)	14.50 (0.57)	14.50 (0.57)
Voice Coil Type/Former	Aluminium	Titanium	Titanium	Titanium
Voice Coil Wire	Hexatech™ Aluminium	Hexatech™ Aluminium	Hexatech™ Aluminium	Hexatech™ Aluminium
DC Resistance (ohm)	3	3.6	3.6	3.6
Voice Coil Induct. @1 kHz (mH)	0.175	0.615	0.615	0.615
Magnet System	Neodymium	Neodymium	Neodymium	Neodymium Double magnet rear vented
HE-Magnetic Gap Height mm (inch)	4	5 (0.20)	5 (0.20)	5 (0.20)
B-Flux Density (T)	0.94	0.66	0.75	0.74
BL Product/BXL	4.2	5.15	6.51	5.15
Max. Linear Ex./Xmax mm (inch)	±3mm(0.12)	±4.75mm (0.18)	±4.75mm (0.18)	±4.75mm (0.18)
Suspension Compliance CMS - mm/N	0.54	0.35	0.67	0.36
Electrical Q Factor QES	0.54	0.63	0.47	0.61
QTS	0.45	0.56	0.43	0.56
QMS	2.66	4.15	7.19	6
Mech. Resistance RMS- N * S / M	1.17	1.32	1	1.2
Moving Mass MMS - gr/ounce	5.3(0.21)	17(0.59)	18(0.63)	30(1.05)
Equiv. Can Air Load VAS - L (cu.ft*)	1.15(0.05)	4.5(0.6)	13.3(0.47)	30.9(1.1)
Effective Piston Area SD sq.cm (sq.inch)	38(1.5)	90(13.95)	120(18.6)	219(33.95)
Cone Type	Triple Layer Cone (TLC)	Triple Layer Cone (TLC)	Triple Layer Cone (TLC)	Triple Layer Cone (TLC)
Cone Material	Carbon Fibre composite	Carbon Fibre composite	Carbon Fibre composite	Carbon Fibre composite
Unit Diameter mm(inch)	100 (3.90)	135 (5.25)	165 (6.50)	222 (8.75)
Mounting Depth mm (inch)	38 (1.50)	60 (2.36)	61 (2.40)	71 (2.80)
Mounting Cutout	83 (3.3)	120 (4.72)	141 (5.55)	192 (7.56)
Net Wight Kg (lb)	0.38 (0.84)	1.05 (2.31)	1.18 (2.60)	1.42 (3.13)

CROSSOVERS	MXT280C	MXT380C
Crossover Point	W: 2500Hz/12dB T: 2500Hz/12dB	W: 450Hz/12dB M: 450Hz/12dB 2700Hz/12dB T: 2700Hz/12dB
Crossover Controls	Tweeter +/- 2dB	Tweeter +/- 2dB Mid 0/- 2dB
Wiring Options	Bi wire / Bi amp	Bi wire / Bi amp

* Morel operates a policy of continuous products design improvement, consequently specifications are subject to alteration without prior notice

MIDS & TWEETERS	MT450	ALTO
Nominal Impedance (ohm)	6	6
Power Handling Wrms	200	220
Max. Trans. Pwr Handling Wrms (10ms)	350	1000
Sensitivity (2.83 V/1M) dB	91	91
Frequency Response Hz	1400-25000	1400-25000
FS Hz	1000	900
Voice Coil Diameter mm (inch)	28 (1.25)	28 (1.125)
Voice Coil Former	Aluminium	Aluminium
Voice Coil Wire	Hexatech™ Aluminium	Hexatech™ aluminium
DC Resistance ohm	5.2	5.2
Magnet System	Neodymium Rear Vented	Neodymium rear chamber underhung
Dome Type	Acuflex™ hand coated soft dome	Acuflex™ hand coated soft dome
Dome Material	Silk	Silk
Unit Diameter mm (inch)	43.00 (1.69)	67.00 (2.6)
Mounting Depth mm (inch)	13.2 (0.52)	32.00 (1.25)
Mounting Cutout mm (inch)	47.00 (2)	55 (2.16)
Net Weight Kg (lb)	0.07 (0.15)	0.35 (0.77)

Active Configuration

Setting up the Elate Carbon system using an external electronic crossover network may very depending on the processor itself, the car cabin acoustic attributes, and the mounting location of the drive units. Choosing proper crossover points and slopes can greatly affect system performance.

The following guidelines should be used to assure each drive unit in the system performs to the highest level. The Optimal Crossover Point/Slope guide should be used for most vehicle applications. Advanced users may refer to the Recommended Crossover Range/Minimum Slope guide for fine system tuning.

Elate Carbon: 53A, 63A, 93A

Optimal Crossover Point/Slope
Tweeter highpass: 3300Hz/12dB
Midrange lowpass: 3300Hz/12dB
Midrange highpass: 450Hz/12dB
Woofer lowpass: 450Hz/12dB
* Woofer highpass: 40Hz/12dB

Recommended Crossover Range/Minimum Slope
Tweeter highpass: 18000Hz-4000Hz/12dB
Midrange lowpass: 18000Hz-4000Hz/6dB
Midrange highpass: 300Hz-750Hz/12dB
Woofer lowpass: 350Hz-750Hz/6dB
* Woofer highpass: 40Hz-80Hz/12dB

* When used with an active subwoofer system.

Elate Carbon: 52A, 62A, 92A

Optimal Crossover Point/Slope
Tweeter highpass: 2000Hz/12dB
Woofer lowpass: 1800Hz/12dB
* Woofer highpass: 60Hz/12dB

Recommended Crossover Range/Minimum Slope
Tweeter highpass: 18000Hz-3000Hz/12dB
Woofer lowpass: 18000Hz-3000Hz/6dB
* Woofer highpass: 40Hz-80Hz/12dB

Wishing you many years of sound enjoyment!



Morel, Ness Ziona, 70400 Israel.
Tel: +972-8-9301161
Fax: +972-8-9301312
E-mail: info@morelhifi.com

Morel America, Chandler, AZ, USA
Toll free number: 1-877-667-3511
Fax: 1-718-721-1560
E-mail: info@morelamerica.com

www.morelhifi.com